


VCXO

SVB, SVC

- Voltage Controlled Crystal Oscillator
- HCMOS/TTL output
- 5.0V & 3.3V supply voltage
- Custom lead length options available
- Wide frequency and pull range



SVB



SVC

DIP TYPE

ELECTRICAL SPECIFICATIONS

Frequency Range	1.000 to 50.000MHz		
Operating Temperature Range	0 to +70°C or -40 to +85°C		
Storage Temperature Range	-40 to +85°C		
Supply Voltage(V _{DD})	5.0V _{DC} ± 5%		3.3V _{DC} ± 5%
Aging (at 25°C)	± 3ppm/year max.		
Load Drive Capability	10 TTL Load or 15pF HCMOS Load		
Start-up Time	10ms max.		
Frequency Deviation / Pin 1 Control Voltage	2.5V _{DC} ± 2.0V _{DC}	± 10, ± 30, ± 50, ± 100ppm min.	
	2.5V _{DC} ± 2.5V _{DC}	± 10, ± 30, ± 50, ± 100, ± 150ppm min.	
	1.65V _{DC} ± 1.65V _{DC} (or ± 1.5V _{DC})	± 10, ± 30, ± 50, ± 100, ± 150ppm min.	
Linearity	± 20, ± 15, ± 10, ± 5%(Optional)		
Input Current	1.000 to 25.000MHz	20mA max.	15mA max.
	25.001 to 50.000MHz	30mA max.	25mA max.
	50.001 to 80.000MHz	40mA max.	35mA max.
	80.001 to 155.520MHz	50mA max.	45mA max.
Frequency Stability	± 50, ± 25, ± 20, ± 10ppm(See Table1.)		
Output Voltage Logic High(V _{OH})	w/TTL Load	2.4V _{DC} min.	
	w/HCMOS Load	90% of V _{DD} min.	
Output Voltage Logic Low(V _{OL})	w/TTL Load	0.4V _{DC} max.	
	w/HCMOS Load	10% of V _{DD} max.	
Duty Cycle	at 50% of Waveform w/HCMOS Load or 1.4V _{DC} w/TTL Load	50 ± 10% (STD) 50 ± 5% (Optional)	
Rise / Fall Time	5ns max.		
Period Jitter : pk-pk	100ps max.		
Period Jitter : One Sigma	25ps max.		

MECHANICAL DIMENSIONS

